

# Polytron 2 XP Ex



ST-1467-2006

The Polytron 2 XP Ex is an explosion proof gas detector for continuous monitoring of combustible gases and vapors in ambient air. The transmitter converts the signal from a catalytic bead or IR sensor to a 4 to 20 mA analog or HART® or RS 485 digital signal output. The unit is designed for one-man calibration, and offers a variety of diagnostics and self test features. The configuration and calibration of the transmitter is menu guided and easy to perform, using either the infrared remote control, the built-in push buttons, or a HART hand held terminal. With the optional relays, Polytron 2 XP Ex can be operated as 'stand alone' unit.



ST-1390-2006

**Polytron 2 XP Ex:**  
Catalytic bead sensor to detect combustible gases and vapors.



ST-1388-2006

**Polytron 2 XP Ex IR:**  
DraegerSensor IR to detect combustible gases and vapors.

### Easy to install

The enclosure provides two mounting holes. For easy wiring, the electronics is enclosed in a 'bucket', and can be pulled out as one unit, held by a tether. The three wire cable, fed through a sealed conduit, is terminated in a pluggable connector at the printed circuit board.

The DraegerSensor IR is the sensor of choice, where 'poisonous' gases might be in the ambient air. Over time, these can damage the catalyst of a catalytic bead sensor, decreasing its sensitivity. In order to reduce maintenance costs for recalibration and exchange, the infrared technology offers a superior solution.

### One man calibration

All setup and maintenance can be performed without opening the transmitter or declassifying the hazardous area. An infrared remote control, beaming through the window, gives full access to the menu and calibration procedure. The menu can also be accessed using the built-in push buttons or a HART hand held terminal. All menu items and messages are displayed in plain English. Other, user selectable languages are French, Spanish and German.

### Stand alone system

With the three built-in relays, Polytron 2 XP Ex can be used as an independent stand alone unit. Two adjustable gas alarm levels and a fault alarm make it convenient to switch warning devices on-site, without having to run cables back and forth to a central controller. The sensor signal can still be transmitted using either the 4 to 20 mA, HART® or RS 485 signal output.

### DraegerSensor technology

Polytron 2 XP Ex offers two sensing principles: catalytic combustion or infrared. The interior design of the catalytic bead sensor offers an extremely high sensitivity. Higher sensitivity also means shorter response times, higher accuracy and improved stability of the sensor signal. The advanced poison resistant DraegerSensor PR has a significantly longer lifetime.

### Features/Benefits:

- Poison resistant catalytic bead sensor
- High performance infrared sensor
- Fast, accurate response
- Non-intrusive calibration
- Backlit LC-Display
- 4 to 20mA, HART, RS 485 interface
- Multidrop capability, reduced wiring costs
- Optional relays on board
- ATEX, UL and CSA\*) approved

## TECHNICAL DATA

Type	Explosion proof transmitter		
Gases and Ranges	Combustible gases and vapors; 0 to 100 %LEL		
Display	Backlit LCD; 2 lines, 20 characters; resolution 1 %LEL Menu structure and messages in real text		
Output Signal	Analog	Normal operation	4 to 20 mA
		Warning, configurable	fault signal every 10 s for 1 s, or off; user programmable
		Maintenance	4 ± 1 mA 1 Hz modulation, or steady; user programmable
		Fault	< 3.2 mA
	Digital	HART®, RS 485	
Relays (optional)	Two alarm relays, one fault relay SPDT; user programmable Rating: 5A 230 VAC, 5A 30 VDC		
Supply Voltage	10 to 32 VDC, 3-wire		
Ambient Conditions	Temperature	40 to + 175 °F / - 40 to + 80 °C *) 40 to + 150 °F / - 40 to + 65 °C **)	
	Pressure	20.7 to 38.4 inch Hg / 700 to 1300 mbar	
	Humidity	0 to 100 %RH	
Enclosure	NEMA 4X & 7, IP 66; 3/4" NPT female conduit entry		
Size (h x w x d, approx.)	7" x 5" x 5" / 180 x 130 x 130 mm *)		
	12" x 5" x 5" / 305 x 130 x 130 mm **)		
Weight (approx.)	4.6 lbs / 2.1 kg *)		
	5.7 lbs / 2.6 kg **)		
Approvals	UL, CSA	Class I, Div 1, Group B, C, D *) Class I, Div 1, Group B, C, D; Class II, Div 1, Group E, F, G **)	
	ATEX	II 2GD EEx d IIC T6/T4, - 40 ≤ T <sub>amb</sub> ≤ + 40 / + 80 °C 0 °C II 2GD EEx d IIC T6/T4, - 40 ≤ T <sub>amb</sub> ≤ + 40 / + 65 °C **)	
	CE-mark	electromagnetic compatibility (directive 89/336/EEC)	

## ORDER INFORMATION

Polytron 2 XP Ex with catalytic bead sensor, without relays; UL version	45 43 005
Polytron 2 XP Ex with catalytic bead sensor and relays; UL version	45 43 000
Polytron 2 XP Ex with catalytic bead sensor, without relays; ATEX, CSA	45 43 060
Polytron 2 XP Ex with catalytic bead sensor and relays; ATEX, CSA	45 43 059
Polytron 2 XP Ex with IR sensor, without relays; UL version	45 43 223
Polytron 2 XP Ex with IR sensor and relays; UL version	45 43 224
Polytron 2 XP Ex with IR sensor, without relays; ATEX version	45 43 227
Polytron 2 XP Ex with IR sensor and relays; ATEX version	45 43 229

\*) with catalytic bead sensor

\*\*) with IR sensor, UL and ATEX approved only

HART® is registered trademark of HCF, Austin, TX

## SYSTEM CENTERS

### CANADA

Draeger Canada Ltd.  
Mississauga, Ontario L5N 6P9  
Tel +1 905 821 8988  
Fax +1 905 821 2565

### P. R. CHINA

Beijing Fortune Draeger  
Safety Equipment Co., Ltd.  
Beijing 101300  
Tel +86 10 80 49 80 00  
Fax +86 10 80 49 80 05

### FRANCE

Dräger Safety France S.A.S.  
67025 Strasbourg Cedex  
Tel +33 388 40 76 76  
Fax +33 388 40 76 67

### GERMANY

Dräger Safety AG & Co. KGaA  
23560 Luebeck  
Tel +49 451 882 0  
Fax +49 451 882 2080

### MEXICO

Draeger Safety S.A. de C.V.  
Querétaro, Qro. C.P. 76148  
Tel +52 442 246 1113  
Fax +52 442 246 1114

### SINGAPORE

Draeger Safety Asia Pte. Ltd.  
139950 Singapore  
Tel +65 68 72 92 88  
Fax +65 67 73 20 33

### UNITED KINGDOM

Draeger Safety UK Ltd.  
Blyth, Northumberland NE24 4RG  
Tel +44 1670 352 891  
Fax +44 1670 540 033

### USA

Draeger Safety, Inc.  
505 Julie Rivers, Suite 150  
Sugar Land, TX 77478  
Tel +1 281 498 1082  
Fax +1 281 498 5190  
www.draeger.com

Dräger Safety AG & Co. KGaA  
Revalstrasse 1  
23560 Luebeck, Germany  
Tel +49 451 882 2794  
Fax +49 451 882 4991  
www.draeger.com